



## SPECIFICATIONS

- **Type:** 8" Dual Cone Air Suspension
- **Voice Coil Impedance:** 8 Ohms
- **Max Power Rating:** 20 Watts
- **Frequency Range:** 50-15,000 Hz
- **Sensitivity:** (1w/1m) 90dB
- **Sound Pressure:** (1m) 97dB
- **Grille Diameter:** 12"
- **Speaker Depth:** 3 1/4"
- **Finish:** White, Baked enamel

## IP-Enabled Overhead Paging Speaker

### EASILY INCORPORATE OVERHEAD PAGING SPEAKERS WITH CISCO IP TELEPHONY SYSTEMS

The Engage Page IPSpeaker assembly consists of an 8" 10-ounce speaker complete with baffle and grille. Each part of the unit is constructed using the highest quality materials and components.

Designed for standard ceiling mounting, the IPSpeaker delivers exceptional tone quality with excellent output clarity. The one-piece speaker baffle, finished in white, works with any interior.

Engage Page IPSpeaker features:

- The first IP-compatible speaker specifically built for use in Cisco IP telephony environments
- Easily integrated into or used to replace current overhead system
- Ideal for use in greenfield deployments
- Reduced administration
- Integrated 20dB gain audio amplification
- Independent volume control

For more information on Engage Paging Products, contact your authorized telecom equipment reseller or TelStrat.

6900 K Avenue | Plano, TX 75074 | USA  
Phone: +1-972-543-3500 (N. America) | +1-972-543-3509 (Central & Latin America)  
+44 (0) 7919 375718 (Europe, Middle East, Africa)  
+61 (0) 4 5004 5722 (Asia Pacific)

[www.telstrat.com](http://www.telstrat.com) | [sales@telstrat.com](mailto:sales@telstrat.com) | [support@telstrat.com](mailto:support@telstrat.com)

